

hinges

automatic closing / single pivot hinge / standard applications

Series M

270° OPENING

Traditional or snap-on assembly of the door



Bright nickel plated die-cast cup and arm.

Sprung hinge (with spring).

Ideal for the most critical applications, where high stability, strength and endurance are required.

They are certified for applications in public environments in conformity with FIRA Level 5 and ANSI Grade 1 requirements.

Adjustments

Compensating side adjustment from -3 mm to +3 mm.

With mounting plates H=0 the negative side adjustment cannot be used.

Height adjustment ± 2 mm.

Depth adjustment with Series 200 mounting plates +2.8 mm.

Depth adjustment with Domi snap-on mounting plates from -0.5 mm to +2.8 mm.

Anti-sliding safety stop.

Mounting plates

Symmetrical and asymmetrical bright nickel plated steel or die-cast Series 200 mounting plates.

Snap-on assembly on Domi mounting plates.

Positioning with pre-determined stop on traditional Series 200 mounting plates.

N.B.: Use POZIDRIVE No. 2 screwdrivers for all screws.

ARTURO SALICE S.p.A. (Società con Unico Socio)

VIA PROVINCIALE NOVEDRATESE, 10
22060 NOVEDRATE (COMO) ITALIA
TEL. 031 790424
FAX 031 791508
info.salice@salice.com

www.salice.com
CAPITALE SOC. € 25.000.000 I.V.
C.F. e P. IVA 00211650130
REG. IMPRESE COMO 00211650130
REA COMO N° 96189

DEUTSCHE SALICE GmbH
74382 NECKARWESTHEIM
www.deutschesalice.de

SALICE UK Ltd.
HUNTINGDON CAMBS PE29 6FN
www.saliceuk.co.uk

SALICE FRANCE S.A.R.L.
06600 ANTIBES
www.salicefrance.com

SALICE CANADA Inc.
MISSISSAUGA, ONTARIO L5L 5Y1
www.salicecanada.com

SALICE AMERICA Inc.
CHARLOTTE NC 28227
www.saliceamerica.com

SALICE ESPAÑA, S.L.U.
08403 GRANOLLERS
www.saliceespana.es

hinges

automatic closing / single pivot hinge / standard applications

Series M

270° OPENING

Traditional or snap-on assembly of the door

CM_3A99

