

Helping you Wear it right



WEARING YOUR 6500 AND 6500QL HALF FACEPIECE RESPIRATOR



Adjust head cradle size as needed to fit comfortably on head. Place the respirator over the mouth and nose with one hand, then pull the head harness over the crown of the head with the other hand.



Grasp the bottom straps, place them at the back of the neck and hook them together.



Pull the ends of the straps to adjust the tightness, beginning with the adjustment points on the head cradle and then moving to the adjustment points at the back of the neck. Do not over-tighten. Strap tension may be decreased by pushing out on back side of buckles.

USING THE 6500QL QUICK LATCH DROP DOWN FEATURE



QUICK LATCH CLOSED



PULL UP ON LATCH



QUICK LATCH OPEN



PULL DOWN ON LATCH

A NOTE ABOUT THE 6500QL: The first time you don a 6500QL Quick Latch Half Facepiece Respirator, make sure the latch is closed. Don according to the instructions above. After the initial donning, once straps are adjusted to the proper length, subsequent donning can be done with the latch initially in the open or closed position. The latch drop down feature should only be used in non-contaminated environments.

TO OPEN QUICK LATCH: Grasp the latch at chin level and pull up. **TO CLOSE QUICK LATCH:** Grasp the facepiece with your thumb on the bottom of the facepiece and your first two fingers on top of the latch. Place the facepiece over your nose and mouth while pushing down on the latch.

USER SEAL CHECKS: CHECK THE SEAL OF YOUR HALF FACEPIECE RESPIRATOR EACH TIME YOU DON THE RESPIRATOR.



POSITIVE PRESSURE USER SEAL CHECK

Place the palm of your hand over the exhalation valve cover and exhale gently. The facepiece should bulge slightly. If air leaks between the face and the facepiece, reposition the respirator and/or adjust the straps for a more secure seal. If you cannot achieve a proper seal, do not enter a contaminated area. See your supervisor.



NEGATIVE PRESSURE USER SEAL CHECK USING DISC FILTERS

Place your thumbs on the center portion of the filters, restricting airflow through the filters, and inhale gently. The facepiece should collapse slightly closer to your face. If air leaks between the face and the facepiece, reposition the respirator and/or adjust the straps for a more secure seal. If you cannot achieve a proper seal, do not enter a contaminated area. See your supervisor.



NEGATIVE PRESSURE USER SEAL CHECK USING CARTRIDGES

Place the palms of your hands over the cartridges and inhale gently. The facepiece should collapse slightly closer to your face. If air leaks between the face and the facepiece, reposition the respirator and/or adjust the straps for a more secure seal. If you cannot achieve a proper seal, do not enter a contaminated area. See your supervisor.



NEGATIVE PRESSURE USER SEAL CHECK USING 7093 FILTERS

Squeeze filter covers with hands toward facepiece to restrict airflow. Be careful not to disturb the position of the respirator. Inhale gently. The facepiece should collapse slightly. If air leaks between the face and the facepiece, reposition it and adjust the straps for a tighter seal. If you cannot achieve a proper seal, do not enter a contaminated area. See your supervisor.



Personal Safety Division
3M Center, Building 235-2W-70
St. Paul, MN 55144-1000

Please recycle. Printed in U.S.A.
© 2013, 3M. All rights reserved.
3M is a trademark of 3M company.
www.3M.com/PPESafety
70-0716-2624-9



This respirator helps reduce exposures to certain airborne contaminants. Before use, the wearer must read and understand the User Instructions provided as a part of the product packaging. Follow all local regulations. In the U.S., a written respiratory protection program must be implemented meeting all the requirements of OSHA 1910.134, including training, fit testing and medical evaluation. In Canada, CSA standard Z94.4 requirements must be met and/or requirements of the applicable jurisdiction, as appropriate. Misuse may result in sickness or death. For proper use, see package instructions, supervisor, or call 3M PSD Technical Service in USA at 1-800-243-4630 and in Canada at 1-800-267-4414.